Amendments to the Claims

1. (Currently Amended) A room for use in conducting medical procedures, comprising:

a magnetic resonance imaging assembly comprising first and second opposed ferromagnetic elements, first and second ferromagnetic pole supports connected to the first and second ferromagnetic elements and first and second poles supported by the first and second pole supports, respectively;

a screen disposed, at least in part, within the magnetic resonance imaging assembly;

a plurality of scenes images on the screen; and means for changing the image a scene for display by moving the screen.

- 2. (Currently Amended) The room of claim 1, wherein the <u>image scene</u> changing means includes means for moving the screen to display a different <u>image scene</u>.
- 3. (Original) The room of claim 2, further comprising a switch for controlling the movement of the screen.
- 4. (Original) The room of claim 1, further comprising a cartridge for containing the screen.

7

5. (Original) The room of claim 4, further comprising means for changing the cartridge.

- 6. (Original) The room of claim 1, wherein the screen is arcuate.
- 7. (Original) The room of claim 1, wherein:

 the first pole support defines a ceiling of the room;

 the second pole support defines a floor of the room; and

 the first and second opposed ferromagnetic elements define opposing

 walls of the room.
- 8. (Currently Amended) The room of claim 6, wherein the <u>a</u> ceiling <u>of the room</u> further comprises lighting disposed proximate to the ceiling.
- 9. (Original) The room of claim 1, wherein the first and second poles are decorated to correspond to an image on the screen.
- 10. (Original) The room of claim 1, further comprising an acoustic means for providing sounds.
- 11. (Original) The room of claim 1, further comprising a scent means for providing smells.

8

12. (Currently Amended) A room for use in conducting medical procedures, comprising:

a magnetic resonance imaging assembly having an imaging volume within the room;

a screen;

at least one <u>a plurality of images</u> on the screen; and

means for moving the screen across the room to display <u>a selected one of</u>

the plurality of images the at least one image.

- 13. (Original) The room of claim 12, wherein the screen further comprises first and second sides, each side comprising at least one image for display in the room.
- 14. (Original) The room of claim 12, wherein the moving means comprises a belt and means for attaching the screen to the belt.
- 15. (Original) The room of claim 14, wherein the attachment means enables separation of the screen and the belt.
- 16. (Original) The room of claim 14, wherein the moving means further comprises a track for guiding the belt across the room.

9

- 17. (Original) The room of claim 16, wherein the track is arcuate.
- 18. (Original) The room of claim 16, wherein the moving means further comprises a pulley system and motor for moving the belt.
- 19. (Original) The room of claim 12, further comprising a window positioned to enable viewing of an image on the screen from a location exterior of the room.
 - 20. (Original) The room of claim 12, further comprising:

 a delivery cartridge; and

 a take-up cartridge;

wherein the screen is stored wound within the delivery cartridge and is moveable by the moving means to the take-up cartridge to be wound within the take-up cartridge during display of an image.

21. (Original) The room of claim 12, further comprising: a delivery cartridge; and

a roller;

wherein the screen has first and second sides and an image on each side, the screen is stored wound within the delivery cartridge, the screen is moveable to the roller to display an image on the first side,

and

the screen is moveable around the roller, in front of the first side, to display an image on the second side.

22. (Original) A room for use in conducting medical procedures, comprising:

a magnetic resonance imaging assembly having a first pole and a second pole within the room;

a screen;

belt;

at least one image on the screen;

a track extending across the room;

a belt movably disposed within the track;

a motor coupled to the belt to cause movement of the belt within the track, across the room; and

a cartridge storing the screen, the screen being attachable to the

wherein movement of the belt causes movement of the screen along the track to display an image in the room.

- 23. (Original) The room of claim 22, further comprising a serrated gear coupled to the motor, wherein the belt has a serrated portion for engaging the serrated gear.
 - 24. (Original) The room of claim 23, further comprising: at least one pulley; and

a torque converter;

the pulley comprising the serrated gear, the pulley being connected to the motor and to the torque converter for selectively controlling a speed of movement of the belt along the track.

- 25. (Original) The room of claim 22, wherein the track is arcuate.
- 26. (Currently Amended) The room of claim 22, further comprising:

a first Velcro® strip <u>comprising a hook and loop material</u> along the belt;

and

a second Velcro® strip comprising a mating hook and loop material along

the screen;

Velcro® strips.

wherein the belt is attachable to the screen by mating the first and second

27. (Currently Amended) A room for use in conducting medical procedures, comprising:

a bed for supporting a patient;

a <u>flexible</u> screen adjacent to the wall;

at least one image on the screen; and

a track extending across the room;

a belt movably disposed within the track; and

moving means for moving the screen <u>along the track</u> to display an image in the room.

- 28. (Original) The room of claim 27, wherein the moving means comprises at least one pulley and a motor coupled to the pulley.
- 29. (Currently Amended) The room of claim 28, wherein the belt is attached to the pulley, the room further comprising:

a belt attached to the pulley; and attachment means for attaching the belt to the screen.

- 30. (Currently Amended) The room of claim 29, further including a track for guiding wherein the track guides the belt across the room.
 - 31. (Original) The room of claim 30, wherein the track is arcuate.
- 32. (Currently Amended) The room of claim 30, wherein the attachment means comprises at least one of a <u>pair of strips comprising a hook and loop material</u>, a hook, a loop, an adhesive, a snap fit, a button, a zipper, a knot, a hinge, a fastener, a bolt, a cable, a clamp, a dowel, a latch, a pin, a seam, a rivet, a screw or a nail.

33. (Original) The room of claim 29, wherein the attachment means is removably attachable.

- 34. (Original) The room of claim 27, further comprising a magnetic resonance imaging assembly with an imaging volume within the room, wherein the screen is viewable to a patient within the imaging volume.
- 35. (Original) A method of preparing a room for a medical procedure, comprising advancing a screen comprising a plurality of images to a selected image.
- 36. (Currently Amended) The method of claim 35 38, wherein the screen is stored in a cartridge, the method comprising advancing the screen from the cartridge.
- 37. (Currently Amended) A method of using a room for a magnetic resonance imaging procedure, comprising:
- (a) moving a screen <u>comprising a plurality of scenes</u>, each scene comprising at least <u>one image</u>, to display <u>a selected one of the scenes</u> an image on the screen, in the room;
- (b) positioning a patient with respect to a magnetic resonance imaging assembly in the room; and
 - (c) performing the magnetic resonance imaging procedure.
 - 38. (Original) The method of claim 37, moving the screen to a selected image.

39. (Currently Amended) The method of claim 41, wherein step (a) the moving is performed prior to the positioning step (b).

- 40. (Original) The method of claim 37, further comprising moving the screen to display a second image.
- 41. (Currently Amended) The method of claim 40, further comprising:

 inserting a second patient into the assembly after moving the screen to display the second image; and

repeating the performing of the magnetic resonance imaging procedure step (c).

- 42. (Original) The method of claim 40, wherein the screen is stored in a cartridge and the second selected image is displayed by replacing a first cartridge by a second cartridge and advancing the screen from the second cartridge to display the second selected image.
- 43. (Original) The method of claim 37, further comprising providing sounds in the room.
- 44. (Original) The method of claim 37, further comprising providing odors in the room.

15

- 45. (Original) The method of claim 37, comprising moving the screen along an arcuate track.
- 46. (Original) The method of claim 37, further comprising providing moving images on the displayed image.
- 47. (Original) The method of claim 37, wherein the image is selected by the patient.
- 48. (Currently Amended) The method of claim 37, further comprising illuminating the a ceiling of the room.
- 49. (Original) The method of claim 37, further comprising illuminating the screen.
- 50. (Original) The room of claim 22, wherein movement of the belt causes movement of the screen out of the cartridge, along the track.
- 51. (Original) The room of claim 50, wherein selective movement of the belt causes selective movement of the screen out of or into the cartridge.

52. (Original) The room of claim 1, further comprising illumination behind the

screen.

53. (Original) The room of claim 22, further comprising:

a ceiling; and

illumination above the ceiling.

- 54. (Original) The room of claim 22, further comprising illumination behind the screen.
- 55. (New) The room of claim 1, wherein each scene comprises at least one image.